


# **Payment API Specification & Integration Guide For Partners**



AirPay

**AirPay (Thailand) Co., Ltd.**

# Version History

Version	Changes	Author	Date
1.0.0	+ Initial creation	Lei Lei	2014-09-29
1.0.1	+ Added get_landing_url API. - Removed API signature. . Changed all API calls to POST.	Lei Lei	2014-10-03
1.0.2	+ Added "from" parameter to get_landing_url API + Added "app" type of the "from" parameter of get_landing_url API. + Added procedure of calling get_landing_url in Mobile App integration workflow. + Added one more order_status: value 101.	Lei Lei	2014-10-07
1.0.3	. Renamed "from" to "source" in get_landing_url API.	Jon	2014-10-09
1.0.4	- Removed app-supplied parameters to return_url for security purpose. + Added instruction of QR Code generation.	Lei Lei	2014-10-10
1.0.5	+ Added order_status 102.	Lei Lei	2014-12-18
1.0.6	- Removed Sandbox order IDs. + Added Sandbox AppID and AppKey.	Lei Lei	2015-01-07
1.0.7	+ Added "msg" field to notify_order_status api.	Lei Lei	2015-03-11
1.0.8	+ Added optional "payment_id" field to get_order_status and notify_order_status api.	Jon	2015-06-26
1.0.9	+ Added order_status 501.	Jon	2015-08-24
1.1.0	+ Added "extra_data" field to order structure	Kwann	2015-10-13
1.2.0	+ Update SSL key	Kwann	2015-10-28
1.3.0	+ Migrate documents to new location, added examples	Kwann	2015-11-24
1.3.1	+ Add QRCode image API	Kwann	2016-01-15
1.3.2	+ Add Refund API	Kwann	2016-03-09

1.3.3	+ Add Update Order API	Kwann	2016-05-04
-------	------------------------	-------	------------

# Table of Contents

- [1. Introduction](#)
- [2. Platforms and Workflows](#)
  - [2.1 PC Web](#)
    - [Usage Scenario](#)
    - [QR Code](#)
    - [Example](#)
    - [Workflow](#)
  - [2.2 Mobile Web](#)
    - [Usage Scenario](#)
    - [Landing URL](#)
    - [Workflow](#)
  - [2.3 Mobile App](#)
    - [Usage Scenario](#)
    - [Landing URL](#)
    - [Mobile SDK](#)
    - [Workflow](#)
  - [2.4 Payment Procedure](#)
- [3. Values and Data Structures](#)
  - [3.1 order\\_id](#)
  - [3.2 app\\_id](#)
  - [3.3 app\\_key](#)
  - [3.4 order\\_validity](#)
  - [3.5 order\\_status](#)
  - [3.6 order](#)
  - [3.7 payment\\_api\\_domain](#)
  - [3.8 payment\\_id](#)
  - [3.9 result\\_code](#)
- [4. API Definitions](#)
  - [4.1 get\\_landing\\_url \(Payment API\)](#)
    - [Request Query Parameters](#)
    - [Response JSON Fields](#)
    - [Example](#)
  - [4.2 get\\_order\\_status \(Payment API\)](#)
    - [Request Query Parameters](#)
    - [Response JSON Fields](#)
    - [Example](#)
  - [4.3 get\\_order\\_details \(Merchant Callback\)](#)
    - [Request Body Parameters](#)
    - [Response JSON Fields](#)
    - [Example](#)
  - [4.4 validate\\_order \(Merchant Callback\)](#)
    - [Request Body Parameters](#)
    - [Response JSON Fields](#)
    - [Example](#)
  - [4.5 notify\\_order\\_status \(Merchant Callback\)](#)

Request Body Parameters  
Response JSON Fields  
Example

- 4.6 refund\_order (Payment API)
  - Request Query Parameters
  - Response JSON Fields
  - Example
- 4.7 update\_order (Payment API)
  - Request Query Parameters
  - Response JSON Fields
  - Example

## 5. API Security

- 5.1 Encryption
- 5.2 API Secret Key

## 6. Sandbox Environment

- 6.1 Purpose
- 6.2 Accessing Method

# 1. Introduction

AirPay is a secure and convenient mobile payment service that allows smartphone users to make direct payment through their bank accounts, credit cards, or counter services.

The Payment API provides a way for any online merchants to collect payment without the hassle of integration with various banks and payment gateways. It serves as the one-stop payment hub for businesses without the resources of developing their own payment gateways.

AirPay serves as one of the payment channels of the merchant. It appears in the "Payment Method Selection" page when the customer checks out from the merchant.

**Note:** This document only contains the Server-to-Server APIs for PC Web and Mobile Web integrations. If you are integrating with the payment API from your Mobile App, please also refer to the Android App and iOS App API documents.

## 2. Platforms and Workflows

The payment API provides integration to the following platforms.

- PC Web
- Mobile Web (iOS and Android)
- Mobile App (iOS and Android)

### 2.1 PC Web

#### Usage Scenario

The merchant may opt to display a QR code on the Payment Method Selection page on the merchant's website. The QR code can be scanned using either the AirPay mobile app (recommended) or via an alternative scanner. The QR code will direct users to the [LandingURL](#) from which users would be prompted to complete their purchase.

#### QR Code


The QR Code is to be generated by the Merchant's website. The free [Google Charts API](#) could be used to generate a QR Code.

#### Example

Landing URL (provided by Payment API)
<code>https://pay.airpay.in.th/pay?order_id=SBIPS_1448261830_311964342&amp;source=qr&amp;app_id=100001&amp;key=nrqL56b9b2e1a9c15b88</code>

QR Code Image URL
<code>https://chart.googleapis.com/chart?chs=200x200&amp;cht=qr&amp;choe=UTF-8&amp;chl=https%3A%2F%2Fpay.airpay.in.th%2Fpay%3Forder_id%3DSBIPS_1448261830_311964342%26source%3Dqr%26app_id%3D100001%26key%3DnrqL56b9b2e1a9c15b88</code>

## Workflow



## **2.2 Mobile Web**


### **Usage Scenario**

At the Payment Method Selection page on the merchant's web site (in a mobile web browser), after the customer has selected AirPay as the payment method, the merchant's web page should redirect the customer to the [LandingURL](#). The landing page would prompt the user to open the AirPay App to complete the payment.

### **Landing URL**

The Merchant's web site needs to open the [LandingURL](#) to launch the AirPay App.

## Workflow



## **2.3 Mobile App**

### **Usage Scenario**

At the Payment Method Selection screen of the merchant's mobile app, after the customer has selected AirPay as the payment method, the merchant's mobile app opens the AirPay mobile app to make the payment, which will then redirect the customer back to the merchant's app after the payment procedure.


### **Landing URL**

The Merchant's App needs to pass the [LandingURL](#) to the Mobile SDK to start the payment.

### **Mobile SDK**


The Merchant App will need to integrate with the AirPay Mobile SDK to handle the inter-app communication.

## Workflow



## 2.4 Payment Procedure

This is a "zoomed-in" look of the "Payment Procedure" step of the above workflows.



# 3. Values and Data Structures

The following values and data structures are used by APIs.

- order\_id
- app\_id
- app\_key
- order\_validity
- order\_status
- order
- payment\_api\_domain
- payment\_id

## 3.1 order\_id

Name	order_id
Type	string
Length	Up to 32 characters max
Description	Merchant-generated ID to identify an order. Must be unique in Merchant's system. Every payment in AirPay must be bound to an order in the Merchant's system.
Note	There are a set of special order_id prefixes used specifically for the <a href="#">Sandbox environment</a> .

## 3.2 app\_id

Name	app_id
Type	uint32
Description	ID to identify a Merchant. Two for each Merchant (one for <a href="#">Sandbox</a> , one for Production).
Note	Please contact your AirPay account manager to obtain this ID.

### **3.3 app\_key**

<b>Name</b>	app_key
<b>Type</b>	string
<b>Description</b>	API key for a Merchant. Two for each Merchant (one for <a href="#">Sandbox</a> , one for Production). Refer to <a href="#">Chapter 5</a> for details.
<b>Note</b>	Please contact your AirPay account manager to obtain this Key.

### **3.4 order\_validity**

<b>Name</b>	order_validity
<b>Type</b>	int32
<b>Description</b>	Validity of an order in the Merchant system.
<b>Note</b>	Values are in the table below. Note that once an order is created, it can only return the following status values.

<b>Value</b>	<b>Description</b>
0	<Reserved>. Do NOT return this value.
200	Order is valid
400	Order does not exist
401	Order has expired

### **3.5 order\_status**

<b>Name</b>	order_status
<b>Type</b>	int32
<b>Description</b>	Status of an order in the AirPay system.
<b>Note</b>	Values are in the table below.

<b>Value</b>	<b>Description</b>
0	<Reserved>. Do NOT return this value.
100	Payment in progress. Payment attempt has started, but not finished yet.
101	Order exists, but payment has not started yet (customer has not yet selected to pay.)
102	Order landing URL has been generated, but not yet opened in AirPay app by customer.
200	Money collected.
201	Money collected, but Merchant API ( <a href="#">notify_order_status</a> ) not accessible. AirPay will retry calling Merchant again. (Note that this value is only used by <a href="#">get_order_status</a> . It's never sent by <a href="#">notify_order_status</a> .)
202	Customer has selected a "Counter Service" as the payment method. Note that this kind of payment methods requires the customer to personally go to the payment counter, therefore it may take minutes to hours before the money can be collected.
300	Order has been canceled by customer. No money was collected.
400	Order does not exist. No money was collected.
401	Order had expired while attempting to collect money. No money was collected.
500	Failed to collect money.
501	Money collected, but refunded, due to merchant cancellation.

### 3.6 order

<b>Name</b>	order
<b>As HTTP Parameters</b>	Expands to HTTP Query Parameters. Each field is one HTTP Query Parameter.
<b>As JSON</b>	An JSON Object. Each field is one JSON field.
<b>Description</b>	The complex data structure with details of an order.
<b>Note</b>	This data structure can be in different forms as stated in the "As" rows above. The actual form depends on the API definition.

Field Name	Field Type	Description
app_id	<a href="#">app_id</a>	The Merchant ID given by AirPay to the Merchant.
order_id	<a href="#">order_id</a>	The Order ID generated by the Merchant.
currency	string	Currency type. AirPay should use "THB"
payable_amount	uint64	Payment amount in the smallest currency unit. AirPay should use Thai Satang (1 THB = 100) Example: 123.50 THB = 12350
expiry_time	uint32	Expiry time for this order. It is the Unix timestamp in seconds (number of seconds from 1970/01/01 00:00:00 GMT).
item_name	string	Product's display name. This can be a brief product description to be displayed to use in AirPay App.
item_image	string	(Optional) Product image URL. Only PNG and JPEG are supported. This image will not be shown in large size, so a smaller image (not larger than 150x150) is preferred.
extra_data	string	(Optional) Additional information to tag with the order, JSON serialized.

### **3.7 payment\_api\_domain**

Country	Domain
Thailand	airpay.in.th

### **3.8 payment\_id**

Name	payment_id
Type	string
Length	Up to 32 characters max
Description	ID generated by Payment API to identify an AirPay payment. Is unique in AirPay system. Every payment in AirPay must be bound to an order in the Merchant's system.
Note	-

### **3.9 result\_code**

Name	result_code
Type	int32
Description	Result of an operation
Note	Values are in the table below.

Value	Description
0	Success
1	API Key or ID is not valid
2	Order does not exist
3	Order was not refunded because it is outside of refund window
4	Order does not meet requirements for this operation
5	An unknown error occurred
6	Order is already refunded
7	An error occurred while updating the order
8	Unable to connect to merchant callback or merchant callback returned negative response

9	API is disabled for this merchant
---	-----------------------------------

# 4. API Definitions

## 4.1 get\_landing\_url (Payment API)

<b>Caller</b>	Merchant Server
<b>Callee</b>	AirPay Server
<b>URL</b>	<a href="https://api.&lt;payment_api_domain&gt;/pay/get_landing_url">https://api.&lt;payment_api_domain&gt;/pay/get_landing_url</a>
<b>Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	The Merchant Server calls this API to get the landing URL for a specific order.

### Request Query Parameters

Name	Type	Description
app_id	<a href="#">app_id</a>	The Merchant ID provided by AirPay.
app_key	<a href="#">app_key</a>	The Merchant Key provided by AirPay.
order_id	<a href="#">order_id</a>	Order ID generated by Merchant.
source	string	'qr', 'qrcode', 'web', or 'app'. <ul style="list-style-type: none"><li>• qr: Returns URL that should be encoded into a QR code. Intended for merchants to generate their own QR codes.</li><li>• qrcode: Returns URL pointing to a QR code image</li><li>• web: Returns URL that should be opened by the user in the web browser</li><li>• app: Returns URL that should be opened within the mobile app</li></ul>
return_url	string	Optional. The URL of Merchant's mobile webpage that will be opened by AirPay App after payment.

### Response JSON Fields

Field Name	Field Type	Description
url	string	Landing URL to be used by <a href="#">Mobile Web</a> and <a href="#">PC Web</a> .

## Example

### Merchant Request (Mobile Web)

```
curl --data "app_id=[app_id]&app_key=[app_key]&order_id=[merchant_order_id]&sou  
rce=web" "http://api.airpay.in.th/pay/get_landing_url"
```

## 4.2 get\_order\_status (Payment API)

<b>Caller</b>	Merchant Server
<b>Callee</b>	AirPay Server
<b>URL</b>	<a href="https://api.&lt;payment_api_domain&gt;/pay/get_order_status">https://api.&lt;payment_api_domain&gt;/pay/get_order_status</a>
<b>Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	The Merchant Server calls this API to get the status of a payment.

### Request Query Parameters

Parameter Name	Parameter Type	Description
app_id	<a href="#">app_id</a>	The Merchant ID given by AirPay to the Merchant.
app_key	<a href="#">app_key</a>	The Merchant Key given by AirPay.
order_id	<a href="#">order_id</a>	Original order ID generated by Merchant.

### Response JSON Fields

Field Name	Field Type	Description
order_status	<a href="#">order_status</a>	Status of the order in AirPay system.
payment_id	<a href="#">payment_id</a>	The payment ID in AirPay system, if payment has been initiated.

### Example

Merchant Request
curl --data "app_id=[app_id]&app_key=[app_key]&order_id=[merchant_order_id]" "http://api.airpay.in.th/pay/get_order_status"

#### 4.3 get\_order\_details (Merchant Callback)

Caller	AirPay Server
Callee	Merchant Server
URL	https://<merchant_url_path>/get_order_details
Method	POST
Req Body	application/x-www-form-urlencoded
Resp Body	JSON
Description	The AirPay Server calls this API to obtain the details of an order.

#### Request Body Parameters

Parameter Name	Parameter Type	Description
app_key	app_key	The Merchant Key given by AirPay.
order_id	order_id	Original order ID generated by Merchant.

#### Response JSON Fields

Field Name	Field Type	Description
order_validity	order_validity	Validity of the order in Merchant's system.
order	order (as JSON)	Order details. If the order_id in the request does not exist in the Merchant's system, this object should be empty but the JSON key MUST exist.

#### Example

Merchant Callback Response
{"order_validity":200,"order":{"app_id":100001,"order_id":1,"currency":"THB","payable_amount":1000,"expiry_time":1448879325,"item_name":"Demo Item","item_image":"","extra_data":"{\\"data\\":\\"additional data\\"}"}}

## 4.4 validate\_order (Merchant Callback)

<b>Caller</b>	AirPay Server
<b>Callee</b>	Merchant Server
<b>URL</b>	<a href="https://&lt;merchant_url_path&gt;/validate_order">https://&lt;merchant_url_path&gt;/validate_order</a>
<b>HTTP Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	The AirPay Server calls this API to validate an order before carrying out each payment attempt.

### Request Body Parameters

Name	Type	Description
app_key	<a href="#">app_key</a>	The Merchant Key given by AirPay.
order_id	<a href="#">order_id</a>	Original order ID generated by Merchant.

### Response JSON Fields

Name	Type	Description
order_validity	<a href="#">order_validity</a>	Validity of the order in Merchant's system.

### Example

Merchant Callback Response
{"order_validity":200}

## 4.5 notify\_order\_status (Merchant Callback)

<b>Caller</b>	AirPay Server
<b>Callee</b>	Merchant Server
<b>URL</b>	<a href="https://&lt;merchant_url_path&gt;/notify_order_status">https://&lt;merchant_url_path&gt;/notify_order_status</a>
<b>HTTP Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	The AirPay Server calls this API to update the final payment status to the Merchant Server. Notes about the final state: If a payment attempt fails and AirPay Server decides to try again, then this "fail" state will not be sent to the Merchant server. The AirPay Server only sends the state after it decides to no longer attempt to collect payment.

### Request Body Parameters

Name	Type	Description
app_key	app_key	The Merchant Key provided by AirPay.
order_id	order_id	Order ID provided by merchant.
order_status	order_status	Status of the payment.
payment_id	payment_id	The payment ID in AirPay system, if payment has been initiated.

### Response JSON Fields

Field Name	Field Type	Description
order_id	order_id	Original order_id in the request. This response value is only used to verify that the Merchant Server is working properly. If this response is not returned, or if the HTTP Response Code is not 200, then the AirPay Server will keep retrying this API until it succeeds.

msg	String	A text message to be shown to the user in the Order Receipt screen in AirPay app. The merchant can use this field to include deliverables such as PIN code. Note: Please do NOT send deliverables if order_status is not successful.
-----	--------	--

## Example

Merchant Callback Response	
{ "order_id":100001,"msg":"Test Order"}	

## 4.6 refund\_order (Payment API)

<b>Caller</b>	Merchant Server
<b>Callee</b>	AirPay Server
<b>URL</b>	<a href="https://api.&lt;payment_api_domain&gt;/pay/refund_order">https://api.&lt;payment_api_domain&gt;/pay/refund_order</a>
<b>Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	Merchant can request a refund on the completed order. A completed order can be refunded if the refund is requested within 30 days of the order creation. <b>Warning:</b> Refunds cannot be reversed.

## Request Query Parameters

Parameter Name	Parameter Type	Description
app_id	<a href="#">app_id</a>	The Merchant ID given by AirPay to the Merchant.
app_key	<a href="#">app_key</a>	The Merchant Key given by AirPay.
order_id	<a href="#">order_id</a>	Original order ID generated by Merchant.

## Response JSON Fields

Field Name	Field Type	Description
code	<a href="#">result_code</a>	A number representing the result of the operation.

## Example

Merchant Request	
curl --data "app_id=[app_id]&app_key=[app_key]&order_id=[merchant_order_id]" "http://api.airpay.in.th/pay/refund_order"	

## 4.7 update\_order (Payment API)

<b>Caller</b>	Merchant Server
<b>Callee</b>	AirPay Server
<b>URL</b>	<a href="https://api.&lt;payment_api_domain&gt;/pay/update_order">https://api.&lt;payment_api_domain&gt;/pay/update_order</a>
<b>Method</b>	POST
<b>Req Body</b>	application/x-www-form-urlencoded
<b>Resp Body</b>	JSON
<b>Description</b>	Used for updating item_name and extra_data information on an order. Order information would be obtained by AirPay via calling the <a href="#">get_order_details</a> merchant callback. <b>Note:</b> This API is not required for regular payment procedure. Please consult AirPay before using this API

### Request Query Parameters

Parameter Name	Parameter Type	Description
app_id	<a href="#">app_id</a>	The Merchant ID given by AirPay to the Merchant.
app_key	<a href="#">app_key</a>	The Merchant Key given by AirPay.
order_id	<a href="#">order_id</a>	Original order ID generated by Merchant.

### Response JSON Fields

Field Name	Field Type	Description
code	<a href="#">result_code</a>	A number representing the result of the operation.

### Example

Merchant Request
curl --data "app_id=[app_id]&app_key=[app_key]&order_id=[merchant_order_id]" "http://api.airpay.in.th/pay/update_order"

# 5. API Security

Security of the Payment API is ensured by both encryption and authentication procedures as described in this section.

## 5.1 Encryption

The Payment API uses industry-standard HTTPS protocol for server identity verification and data encryption.

Save the content of the following table to a file and use in your server code.

**Note:** Please use the appropriate certificate for the relevant service.

AirPay
-----BEGIN CERTIFICATE----- MIIDVDCCAjygAwIBAgIDAjRWMA0GCSqGSIb3DQEBCQUAMEIxCzAJBgNVBAYTAiVT MRYwFAYDVQQKEw1HZW9UcnVzdCBJbmMuMRswGQYDVQQDExJHZW9UcnVzdC BHbG9i YWwgQ0EwHhcNMDIwNTIxMDQwMDAwWhcNMjIwNTIxMDQwMDAwWjBCMQswCQY DVQGG EwJVUzEWMBQGA1UEChMNR2VVHJ1c3QgSW5jLjEbMBkGA1UEAxMSR2VVHJ1c3 Qg R2xvYmFsIENBMIIBljANBgkqhkiG9w0BAQEFAOCAQ8AMIIBCgKCAQEA2swYYzD9 9BcjGIZ+W988bDjkcbd4kdS8odhM+KhDtgPpTSEHCljaWC9mOSm9BXiLnTjoBbdq fnGk5sRgprDvgOSJKA+eJdbtg/OtppHHmMICGDUUna2YRpluT8rxh0PBfpVXLVDv iS2Aelet8u5fa9IAjbkU+BQVNdnARqN7csiRv8lVK83QlZ6cJmTM386DGXHKTubU 1XupGc1V3sjs0I44U+VcT4wtIAjNvxm5suOpDkZALeVAjmRCw7+OC7RHQWa9k0+ bw8HHA8sHo9gOeL6NIMTOdReJivbPagUvTLrGAMoUgRx5aszPeE4uwc2hGKceeo W MPRfwCvocWvk+QIDAQABo1MwUTAPBgnVHRMBAf8EBTADAQH/MB0GA1UdDgQW BBTA ephojYn7qwVkBDF9qn1luMrMTjAfBgNVHSMEGDAWgBTephoyYn7qwVkBDF9qn1I uMrMTjANBgkqhkiG9w0BAQUFAOCAQEAnMpauUvXVSOKVCUn5kaFOSPeCpilKln Z57QzxpeR+nBsqtP3UEaBU6bS+5Kb1VSsyShNwrrZHqLizz/Tt1kL/6cdjHPTfS tQWVYrm3ok9Nns4d0iXrKYgjy6myQzCspIFAMfOEVEiluCI6rYVSAlk6I5PdPcF PseKUgzbFbS9bZvlxrFuaknjaZC2mqUPuLk/IH2uSrW4nOQdtqvmIKXBx4Ot2/Un hw4EbNX/3aBd7YdStysVAq45pmp06drE57xNNB6pXE0zX5IJL4hmXXeXxx12E6nV 5fEWCRE11azbJHFwLJhWC9kXtNHjUStedejV0NxPNO3CBWaAocvmMw== -----END CERTIFICATE----- -----BEGIN CERTIFICATE----- MIIEJTCCAw2gAwIBAgIDAjp3MA0GCSqGSIb3DQEBCwUAMEIxCzAJBgNVBAYTAiVT MRYwFAYDVQQKEw1HZW9UcnVzdCBJbmMuMRswGQYDVQQDExJHZW9UcnVzdC BHbG9i YWwgQ0EwHhcNMTQwODI5MjEzOTMyWhcNMjIwNTIwMjEzOTMyWjBHMQswCQYDV QQG EwJVUzEWMBQGA1UEChMNR2VVHJ1c3QgSW5jLjEgMB4GA1UEAxMXUmFwaWRT

U0wg  
U0hBMjU2IENBIC0gRzMwggEiMA0GCSqGSib3DQEBAQUAA4IBDwAwggEKAoIBAQCV  
v  
VJvZWF0eLFbG1eh/9H0WA/Qi1rkjqfdVC7UBMBdmJyNkA+8EGVf2prWRHzAn7Xp  
SowLBkMEu/SW4ib2YQGRZjEiwzQ0Xz8/kS9EX9zHFLYDn4ZLDQp/oIACg8PTH2IS  
1p1kD8mD5xvEcKyU58Okaiy9uJ5p2L4KjxZjWmhgxHsw3hUEv8zTz5IBVV6s9cQ  
DAP8m/0Ip4yM26eO8R5j3LMBL3+vW8M8SKeDaCGnL+enP/C1DPz1hNFTvA5yT2AM  
QriYrRmIV9cE7le/fodOoyH5U/02mEiN1vi7SPipyGTRzFRIU4uvt2Uevy kzKdkp  
YEj4/5G8V1jINS67abZZAgMBAAGjggEdMIIBGTafBgNVHSMEGDAwgBTaeph0jYn7  
qwVkBDF9qn1luMrMTjAdBgNVHQ4EFgQUw5zz/NNGCDS7zkZ/oHxb8+lly1kwEgYD  
VR0TAQH/BAgwBgEB/wIBADAObgNVHQ8BAf8EBAMCAQYwNQYDVR0fBC4wLDAqo  
Cig  
JoYkaHR0cDovL2cuc3ltY2luY29tL2NybHMvZ3RnbG9iYWwuY3JsMC4GCCsGAQUF  
BwEBBClIDAeBggrBqEFBQcwAYYSaHR0cDovL2cuc3ltY2QuY29tMEwGA1UdIARF  
MEMwQQYKYIZIAYb4RQEHNjAzMDEGCCsGAQUFBwIBFIVodHRwOi8vd3d3Lmdlb3R  
y  
dXN0LmNvbS9yZXNvdXJjZXMY3BzMMA0GCSqGSib3DQEBCwUA4IBAQCjWB7GQzK  
s  
rC+TeLfqrIRARy1+eI1Q9vhmrNZPc9ZE768LzFvB9E+aj0I+YK/CJ8cW8fuTgZCp  
fO9vfm5FIBaEvetJ8cQO9K8EWYOHDyw7I8NaEpt7BDV7o5UzCHuTcSJCs6nZb0+B  
kwHtnm8hEqddwnxxYny8LScVKoSew26T++TGezvfU5ho452nFnPjJSxhJf3GrkH  
uLLGTxN5279PURt/aQ1RKsHWFf83UTRIUfQevjhq7A6rvz17OQV79PP7GqHQyH5O  
ZI3NjGFVkp46yl0ID/gdo0p0V8aVUBwdSWmMy66S6Vdu5oNMOGNX2Es8zvsJmh  
gP8L8mJMCCaY  
-----END CERTIFICATE-----  
-----BEGIN CERTIFICATE-----  
MIIE1DCCA7ygAwIBAgISeSF/duG7H12FLtBzxjKhMj3wMA0GCSqGSib3DQEBCwUA  
MEwxCzAJBgNVBAYTAkJFMRkwFwYDVQQKExBhbG9iYWxTaWduIG52LXNhMSIwIAY  
D  
VQQDEXlBbHBoYVNTCBDQSAtlFNlQTI1NiAtIEcYMB4XDTE0MTAwMTA0MTQ1NloX  
DTE5MTAwMTA0MTQ1NlowPDEhMB8GA1UECxMYRG9tYWluIENvbnnRyb2wgVmFsa  
WRh  
dGVkMRcwFQYDVQQDDA4qLmFpcnBheS5pbis50aDCCASlwDQYJKoZlhvcNAQEBBQ  
AD  
ggEPADCCAQoCggEBAMDqltr+f3kOHXCPJCPRCxoRMCAvE1JnT/pfuaZ2o+5p079ID  
GHI2B5vr8gom2NWYO6E/3IQXS8+/mrsHs0BI0bmVW6+wKvrv7hF2qNKGcz1dMBx  
qkqmfmzXrLDhn7OIC0VdD3Spv8er5kharoah41a04yC5r5c+gSfwqUYxbWEY5iKt  
zQ8p2LEsZL/AXkV8ImoWHmTZJhkNVqrNm/PySHjygBXgJVYwfkm7xitExNZ/ia  
GQQn0x6NliGHvELn6FqIj1FDLTGITSOeV8nT+Ov3II0UUEW2jeILC41NkX7gfgL  
qYO1FBar0taNI837KrWwv1oQ4k3R9PO/Jchnb7UCAwEAAaOCAb4wggG6MA4GA1Ud  
DwEB/wQEAvIFoDBJBgNVHSAEQjBAMD4GBmeBDAECATA0MDIGCCsGAQUFBwIB  
FiZo  
dHRwczovL3d3dy5nbG9iYWxzaWduLmNvbS9yZXvcl0b3J5LzAnBgNVHREEIDAe  
gg4qLmFpcnBheS5pbis50aIIMYWlycGF5LmluLnRoMAkGA1UdEwQCMAAwHQYDVR0I  
BBYwFAYIKwYBBQUHAwEGCCsGAQUFBwMCMD4GA1UdHwQ3MDUwM6AxoC+GL  
Wh0dHA6  
Ly9jcmwyLmFscGhhc3NsLmNvbS9ncy9nc2FscGhhc2hhMmcyLmNybDCBiQYIKwYB  
BQUHAQEEfTB7MEIGCCsGAQUFBzACHjZodHRwOi8vc2VjdXJIMi5hbHBoYXNzbC5j

```
b20vY2FjZXJ0L2dzYWxwaGFzaGEyZzJyMS5jcnQwNQYIKwYBBQUHAGGKWh0dHA6
Ly9vY3NwMi5nbG9iYWxzaWduLmNvbS9nc2FscGhhc2hhMmcyMB0GA1UdDgQWB
-----END CERTIFICATE-----
```

## 5.2 API Secret Key

Two Secret Keys (one for [Sandbox](#), one for Production) are created for each merchant. Both AirPay and the Merchant knows this Secret Key for this specific Merchant. This is the "shared secret". For each API call, the caller (both AirPay or Merchant) appends this secret key in the POST parameters ([app\\_key](#)), and the callee validates the legitimacy of the caller by validating this key.

The merchant can contact AirPay customer service to obtain the Secret Key.

# **6. Sandbox Environment**

## **6.1 Purpose**

To help merchants to develop and test the integration, AirPay has set up a Sandbox environment with the exact same procedure as the production environment but without actually deducting money from the associated testing accounts. The merchant should integrate and test with the Sandbox first, before releasing the service to actual customers.

## **6.2 Accessing Method**

The merchant uses the Sandbox app\_id + app\_key to access the Sandbox. The orders in Sandbox will NOT deduct money from the AirPay account.